QNAP

QNAP TS-h987XU-RP NAS Rack (1U) Intel Xeon E E-2334 16 GB DDR4 48 TB QuTS hero Black, Silver

Brand : QNAP **Product code:** TS-H987XU-RP-E2334-16G/48TB-

EXO

Product name: TS-h987XU-RP

iSCSI support

Intel Xeon E-2334, 16 GB ECC DDR4, 5GB Flash, 4 x 3.5" + 5 x 2.5" U.2, RJ-45, USB 3.2 Gen 2, 2 x 300W PSU, 8.43 kg

QNAP TS-h987XU-RP. Type: NAS. Chassis type: Rack (1U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2334, Processor frequency: 3.4 GHz. Internal memory: 16 GB, Internal memory type: DDR4. Total installed storage capacity: 48 TB. Operating system installed: OuTS hero.





Storage		Performance	
Supported storage drive interfaces	Serial ATA, U.2	Device class *	Large Enterprise Business
Storage drive sizes supported	2.5,3.5"	Backup function *	✓
RAID support *	✓	Backup features	iscsi lun
RAID levels	0, 1, 5, 6, 10, 50, 60	Multilingual support	1
Online RAID expansion	✓	Snapshot	1
RAID rebuild	1	Security algorithms	256-bit AES, FIPS 140-2
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	Access Control List (ACL) Reset button	1
Storage drives installed *	×	On/off switch	4
Total installed storage capacity *	48 TB	Built-in FTP server	4
Number of storage drives supported		Built-in FTP Server	Annia Cafari Caagla Chrama
*	9	Browser supported	Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Installed storage drive type *	X	System log	1
Supported storage drive types *	HDD & SSD	Hot spare	1
Disk roaming	1	Disk scan	1
Processor		S.M.A.R.T. support	1
Processor manufacturer *	Intel	Share folder	Thick, Thin
Processor family *	Intel Xeon E	Software	
Processor model *	E-2334	Operating system installed *	OuTS hero
Processor frequency *	3.4 GHz	Operating system version	h5.0.0
Processor boost frequency	4.8 GHz	2,71	Windows 10, Windows 10
Processor cores	4		Education, Windows 10 Education
Processor threads	8		x64, Windows 10 Enterprise, Windows 10 Enterprise x64,
Processor cache	8 MB		Windows 10 Home, Windows 10
CPU configuration (max)	1		Home x64, Windows 10 IOT Core,
Memory			Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro
Internal memory *	16 GB		x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7,
Internal memory type	DDR4		Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7
Maximum RAM supported	128 GB	Windows operating systems	Enterprise x64, Windows 7 Home
Memory slots	4	supported	Basic, Windows 7 Home Basic x64, Windows 7 Home Premium,
Memory form factor	UDIMM		Windows 7 Home Premium, Windows 7 Home Premium x64,
ECC	✓		Windows 7 Professional, Windows 7
Flash memory	5000 MB		Professional x64, Windows 7 Starter, Windows 7 Starter x64,
Network			Windows 7 Ultimate, Windows 7
Ethernet LAN *	✓		Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise,
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s	Windows 8 Enterprise x64, Wind	
Ethernet LAN data rate supported (max)	10000 Mbit/s		8 Pro, Windows 8 Pro x64, Windows 8 x64
DHCP server	1		
	•		

Network		Software	
Wake-on-LAN ready Supported network protocols Dynamic DNS (DDNS)	✓ IPv4, IPv6 ✓	Linux operating systems supported	Debian 7.0, Red Hat Enterprise Linux WS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, SuSE Linux 15, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 15.04, Ubuntu 16.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04 LTS, Ubuntu 22.04 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Ports & interfaces		Emax operacing systems supported	
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Concurrent connections PCI Express x8 (Gen 4.x) slots	4 4 10000 1	Mac operating systems supported	
Design	5 1 (41)		
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (1U) Active Black, Silver 4 fan(s) 4 cm	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, Solaris 10, Solaris 10
LED indicators	HDD, LAN, Status	Other operating systems supported	SPARC, Solaris 11, Solaris 11 SPARC
Performance		Power	
Type *	NAS	Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (sleep)	250 W 2 120.58 W 114.6 W
		Weight & dimensions	
		Width * Depth * Height * Weight Package weight	430 mm 479 mm 43.3 mm 8.43 kg 11.1 kg
		Packaging content	
		Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 2 52
		Processor special features	
		Enhanced Intel SpeedStep Technology	1
		Execute Disable Bit Idle States	1
		Intel 64	,
		Intel Trusted Execution Technology	✓
		Intel Virtualization Technology (VT-x)	✓
		Intel Virtualization Technology for Directed I/O (VT-d)	1
		Intel VT-x with Extended Page Tables (EPT)	✓
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

