

## **QNAP TVS-672XT NAS Tower Ethernet LAN Black i3-8100T**





**Brand**: QNAP Product code: TVS-672XT-I3-8G-72TB-EXOS

**Product name:** TVS-672XT



Intel Core i3-8100T 3.1 GHz, DDR4 SODIMM, 4 GB Flash, Intel UHD Graphics 630, 6 x 3.5" SATA, 2 x M.2, 1 x 10GBASE-T RJ45, 1 x USB 3.0, 2 x Type-C USB 3.1 Gen2, 2 x Type-A USB 3.1 Gen2, 1 x HDMI 2.0, 250W

QNAP TVS-672XT. Total installed storage capacity: 72 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: Intel® Core™ i3, Processor manufacturer: Intel, Processor model: i3-8100T. Internal memory: 8 GB, Internal memory type: DDR4, Maximum RAM supported: 32 GB. Ethernet LAN data rates: 10,100,1000,1200,2500,5000,10000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s, Supported network protocols: TCP/IP, IPv4, IPv6. On-board graphics card base frequency: 350 MHz, On-board graphics card dynamic frequency (max): 1100 MHz, On-board graphics card ID: 0x3E91

| Storage                               |                                      | Design                                  |  |
|---------------------------------------|--------------------------------------|---|--|
| Supported storage drive interfaces    | M.2, Serial ATA III                  | Built-in display                        | ✓  |
| Storage drive sizes supported         | 2.5,3.5,M.2                          | Cable lock slot                         | ✓  |
| Number of M.2 (M & B) slots           | 2                                    | Cable lock slot type                    | Kensington   |
| RAID support *                        | ✓                                    | Built-in speaker(s)                     | ✓  |
| RAID levels                           | 0, 1, 5, 6, 10, 50, JBOD             | Number of built-in speakers             | 1  |
| Online RAID migration                 | ✓                                    | Performance                             |  |
| Online RAID expansion                 | ✓                                    | Type *                                  | NAS  |
| Hot-swap drive bays                   | ✓                                    | Device class *                          | Home & Home Office   |
| Supported file systems                | FAT32, HFS+, NTFS, exFAT, ext3, ext4 | Backup function *                       | <b>✓</b>   |
| Storage drives installed *            | ✓                                    | Backup features                         | iscsi lun  |
| Total installed storage capacity *    | 72 TB                                | Buzzer                                  | ✓  |
| Number of storage drives supported    | <sup>d</sup> 6                       | Multilingual support                    | ✓  |
| *                                     | -                                    | Noise level                             | 23.8 dB  |
| Installed storage drive type *        | HDD                                  | Snapshot                                | ✓  |
| Supported storage drive types *       | HDD & SSD                            | Management protocols                    | SNMP 2/3   |
| Auto-rebuild                          | <b>✓</b>                             | Web-based management                    | ✓  |
| Bad block scan Disk roaming           | 1                                    | Share folder access right<br>management | ✓  |
| Processor                             |                                      | Security algorithms                     | 256-bit AES, FIPS 140-2, HTTPS, SSH  |
|                                       |                                      | Access Control List (ACL)               | ✓  |
| Processor manufacturer *              | Intel                                | Reset button                            | 1  |
| Processor generation                  | 8th gen Intel® Core™ i3              | On/off switch                           | 1  |
| Processor family *                    | Intel® Core™ i3                      | Built-in iTunes server                  | 1  |
| Processor model *                     | i3-8100T                             | Built-in FTP server                     | ✓  |
| Processor frequency * Processor cores | 3.1 GHz<br>4                         | Browser supported                       | Apple Safari 7, Google Chrome,<br>Microsoft Internet Explorer 10,<br>Mozilla Firefox |
| Processor threads                     | 4                                    | System log                              | ✓  |
| Processor cache                       | 6 MB                                 | Hot spare                               | <b>,</b>   |
| Bus type                              | DMI3                                 | S.M.A.R.T. support                      | ,  |
| Configurable TDP-down frequency       | 2.4 GHz                              | Share folder                            | CIFS/SMB   |
| CPU configuration (max)               | 1                                    | Universal Plug and Play (UPnP)          | ✓  |
| ECC supported by processor            | 1.16 1.0 ( 2.4 2.0                   |   | •  |
| PCI Express configurations            | 1x16, 1x8+2x4, 2x8                   | Software                                |  |
| PCI Express slots version             | 3.0                                  | Operating system installed *            | QNAP Turbo System  |
| Processor cache type                  | Smart Cache                          | Operating system version                | 4.4.0  |
| Processor code Processor codename     | SR3Y8                                |   |  |
|                                       | Coffee Lake<br>14 nm                 |   |  |
| Processor inthography                 | 64-bit                               |   |  |
| Processor operating modes             | 64-DIT<br>37.5 x 37.5 mm             |   |  |
| Processor package size                |                                      |   |  |
| Processor socket                      | LGA 1151 (Socket H4)                 |   |  |
| Scalability                           | 1S                                   |   |  |
| Stepping                              | В0                                   |   |  |

|   |  | 0.6   |  |
|---|--|---|--|
| Processor   |  | Software  |  |
| System bus rate Tjunction Thermal Design Power (TDP) On-board graphics card model Maximum internal memory supported by processor Memory bandwidth supported by processor (max)  Memory Internal memory type Maximum RAM supported Memory slots Internal memory * Flash memory | 8 GT/s 82 °C 35 W Intel® UHD Graphics 630 64 GB 37.5 GB/s  DDR4 32 GB 2 x SO-DIMM 8 GB 4000 MB | Windows operating systems supported                                 | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8, Windows 8, Windows 9, |
| Network   |  |   | Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows  |
| Ethernet LAN *  | 10 100 1000 1200 2500 5000 10000   |   | 8 x64  |
| Ethernet LAN data rates   | 10,100,1000,1200,2500,5000,10000<br>Mbit/s   | Linux operating systems supported                                   | Mac OS V 10 10 Vacamita Mac OS V   |
| Ethernet LAN data rate supported (max) Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support   | 10000 Mbit/s  X  ✓   | Mac operating systems supported  Server operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows Server 2012, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016  |
| Wake-on-LAN ready   | <b>✓</b>   |   | Windows Server 2016  |
| Supported network protocols  Link aggregation   | TCP/IP, IPv4, IPv6 ✓   | Power   |  |
| Load balancing system   | 7  | Power supply unit (PSU) capacity                                    | 250 W  |
| Dynamic DNS (DDNS)  | <b>√</b>   | AC input voltage<br>Fan voltage                                     | 100 - 240 V<br>12 V  |
| WLAN adapter supported  | ✓  | Weight & dimensions   | 12 4   |
| Ports & interfaces  |  | Width *   | 264.3 mm   |
| USB port *  | ✓  | Depth *   | 279.6 mm   |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A  | 1  | Height *  | 188.2 mm   |
| ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A   |  | Packaging content   |  |
| ports quantity  | 2  | Cables included   | AC, LAN (RJ-45)  |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity   | 2  | Quick installation guide  | ✓  |
| HDMI ports quantity   | 1  | Processor special features  |  |
| HDMI version  | 2.0  | Embedded options available  | ✓  |
| Ethernet LAN (RJ-45) ports *  | 3  | Enhanced Intel SpeedStep  | ✓  |
| Thunderbolt 3 ports quantity 3.5 mm (1/8-inch) out  | 2  | Technology  Execute Disable Bit                                     | /  |
| PCI Express x4 (Gen 3.x) slots  | 1  | Idle States   | <b>V</b>   |
| Microphone in   | 1  | Intel 64  | ✓  |
| Graphics  |  | Intel Clear Video Technology  | <b>√</b>   |
| On-board graphics card base   | 250 MH-  | Intel Enhanced Halt State   | ✓  |
| frequency   | 350 MHz  | Intel Identity Protection Technology version                        | 1.00   |
| On-board graphics card dynamic frequency (max)  | 1100 MHz   | Intel Secure Key Technology version                                 |  |
| On-board graphics card DirectX version  | 12.0   | Intel Stable Image Platform Program (SIPP)                          | ^  |
| On-board graphics card OpenGL version   | 4.5  | Intel Stable Image Platform Program (SIPP) version                  | 0.00   |
| On-board graphics card ID   | 0x3E91   |   | X  |
| Maximum on-board graphics card  | 64 GB  | Intel TSX-NI  | 0.00   |
| memory  | V-7 VID  | Intel TSX-NI version Intel Virtualization Technology (VT-           | 0.00   |
| Number of displays supported (on-<br>board graphics)  | 3  | x)  | 1  |
|   |  | Intel Virtualization Technology for Directed I/O (VT-d)             | ✓  |

| Design                                     |                             | Processor special features  |            |
|--|-----------------------------|---|------------|
| Fan diameter 9.2 cm<br>Fan diameter 2 6 cm |                             | Intel VT-x with Extended Page<br>Tables (EPT)                                       | 1          |
|  | Black<br>4 fan(s)<br>9.2 cm | Intel® AES New Instructions (Intel® AES-NI)   | 1          |
|  |                             | Intel® Clear Video HD Technology<br>(Intel® CVT HD)                                 | 1          |
|  |                             | Intel® Clear Video Technology for<br>Mobile Internet Devices (Intel CVT<br>for MID) | <b>√</b>   |
|  |                             | Intel® Hyper Threading Technology (Intel® HT Technology)                            | ×          |
|  |                             | Intel® Identity Protection<br>Technology (Intel® IPT)                               | ✓          |
|  |                             | Intel® InTru™ 3D Technology   | ✓          |
|  |                             | Intel® OS Guard   | ✓          |
|  |                             | Intel® Quick Sync Video Technology  | ✓          |
|  |                             | Intel® Secure Key   | ✓          |
|  |                             | Intel® Smart Cache  | ✓          |
|  |                             | Intel® Turbo Boost Technology   | ×          |
|  |                             | Maximum number of PCI Express lanes   | 16         |
|  |                             | Thermal Monitoring Technologies   | ✓          |
|  |                             | Thermal solution specification  | PCG 2015A  |
|  |                             | Memory channels supported by processor  | Dual       |
|  |                             | Memory types supported by processor   | DDR4-SDRAM |
|  |                             | Operational conditions  |            |
|  |                             | Operating temperature (T-T)   | 0 - 40 °C  |
|  |                             | Other features  |            |
|  |                             | Digital Living Network Alliance (DLNA) certified                                    | ✓          |
|  |                             | Processor ARK ID  | 129944     |

