QNAP

Product name : TS-1673AU-RP

Dynamic DNS (DDNS)

QNAP TS-1673AU-RP NAS Rack (3U) Ryzen Embedded V1500B 16 GB DDR4 224 TB HDD QNAP Turbo System Black, Grey

Brand: QNAP Product code: TS-1673AU-RP-16G/224TB-REDPLUS

AMD Ryzen Embedded V1500B, 16 GB UDIMM DDR4 (1 x 16 GB), 5 GB Flash, 16 x 3.5-inch SATA 2/3, 132 \times 482 \times 425 mm, 550W (x2) PSU, 100 - 240V

QNAP TS-1673AU-RP. Type: NAS. Chassis type: Rack (3U). Device class: Small & Medium Business. Processor family: Ryzen Embedded, Processor model: V1500B, Processor frequency: 2.2 GHz. Internal memory: 16 GB, Internal memory type: DDR4. Total installed storage capacity: 224 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System



Storage		Ports & interfaces	
Storage drive size Storage drive sizes supported	2.5/3.5" 2.5,3.5"	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity Ethernet LAN (RJ-45) ports *	1 2 2
RAID support *	0.1 5 6 10 50 60 1000	Design	
RAID levels Hot-swap drive bays Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported *	16	Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (3U) Active Black, Grey 3 fan(s) 8 cm HDD, LAN, Power, Status, USB
Installed storage drive type * Supported storage drive types *	HDD & SSD	Performance	
Processor Processor manufacturer * Processor family *	AMD Ryzen Embedded V1500B	Type * Device class * Backup function * Backup features Multilingual support	NAS Small & Medium Business ✓ Cloud, iSCSI LUN
Processor frequency *	2.2 GHz	Software	
Processor cores Processor threads L2 cache L3 cache	4 8 2 MB 4 MB	Operating system installed * Operating system version Windows operating systems	QNAP Turbo System 4.4.2 Windows 10, Windows 7, Windows 8
Memory		supported Linux operating systems supported	√
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	16 GB DDR4 32 GB 2 DIMM 5000 MB	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina Windows Server 2008 R2, Windows
·	3000 FID		Server 2008 R2 x64, Windows Server 2012, Windows Server 2012
Network Ethernet LAN * Ethernet LAN data rates DHCP client	10,100,1000,2500 Mbit/s	Server operating systems supported	
DHCP server	· ✓	Other operating systems supported	Solaris 10
Jumbo frames support	✓	Power	
iSCSI support	√	Power supply location	Built-in
LIVE SMIC LINE (LILINE)			

Power supply unit (PSU) capacity Number of power supply units

550 W

2

Ports & interfaces		Power	
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Power consumption (typical) Power consumption (sleep) AC input voltage	97.34 W 47.75 W 100 - 240 V
		Weight & dimensions	
		Width *	482 mm
		Depth *	425 mm
		Height *	132 mm
		Weight	12 kg
		Package weight	17.1 kg
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

