



QNAP TVS-872XT-i5-16G 16TB (Seagate Exos) 8-Bay NAS; Intel core i5-8400T 6-core 1.7 GHz Processor(max 3.3 Tower Ethernet LAN Black



Brand : QNAP

Product code: TVS-872XT-I5-16G/16TB-EXOS

Product name : TVS-872XT-i5-16G 16TB (Seagate Exos)
8-Bay NAS; Intel core i5-8400T 6-core 1.7 GHz Processor(max 3.3

- High-speed Thunderbolt™ 3 with SMB protocol, allowing Mac® and Windows® users to collaborate on media editing
- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices
- PCIe expandability allows the use of an entry-level graphics card to accelerate NAS video processing and GPU computing
- Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency
- 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i5-8400T 1.7 GHz, DDR4, 8x 2.5/3.5" SATA III, 2x M.2, 1x 10G RJ-45, 2x 1G RJ-45, 2x PCIe, USB 3.0, 2x USB 3.1 C, 2x USB 3.1 A, HDMI 2.0, 2x 3.5mm, 188.2x329.3x279.6 mm

Storage		Performance	
Supported storage drive interfaces	Serial ATA III	Type *	NAS
Storage drive sizes supported	2.5,3.5"	Device class *	Small & Medium Business
Number of M.2 (M & B) slots	2	Backup function *	✓
RAID support *	✓	Backup features	Cloud, iSCSI LUN
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Buzzer	✓
Online RAID migration	✓	Multilingual support	✓
Online RAID expansion	✓	Web-based management	✓
RAID rebuild	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv3, SSH, SSL/TLS
Hot-swap drive bays	✓	Access Control List (ACL)	✓
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Reset button	✓
Storage drives installed *	✓	On/off switch	✓
Number of storage drives supported *	8	Built-in iTunes server	✓
Installed storage drive type *	HDD	Built-in FTP server	✓
Supported storage drive types *	HDD & SSD	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Bad block scan	✓	System log	✓
Processor		Hot spare	✓
Processor frequency *	1.7 GHz	S.M.A.R.T. support	✓
Processor boost frequency	3.3 GHz	Share folder	CIFS/SMB
Processor cache	9 MB	Universal Plug and Play (UPnP)	✓
Bus type	DMI3	USB copy function	✓
Configurable TDP-down frequency	1.2 GHz	Software	
CPU configuration (max)	1	Operating system version	4.4.0
ECC supported by processor	✗	Windows operating systems supported	Windows 10, Windows 7, Windows 8
PCI Express configurations	1x16, 1x8+2x4, 2x8	Linux operating systems supported	✓
PCI Express slots version	3.0	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Processor cache type	Smart Cache	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Processor code	SR3X6		
Processor lithography	14 nm		
Processor operating modes	64-bit		
Processor package size	37.5 x 37.5 mm		
Scalability	1S		
Stepping	U0		
System bus rate	8 GT/s		
Tjunction	100 °C		

Processor		Power	
Thermal Design Power (TDP)	35 W	Power supply location	Built-in
Maximum internal memory supported by processor	64 GB	Power supply unit (PSU) capacity	250 W
Memory bandwidth supported by processor (max)	41.6 GB/s	Number of power supply units	1
Conflict-Free processor	✓	AC input voltage	100 - 240 V
Memory		Weight & dimensions	
Internal memory type	DDR4	Width *	329.3 mm
Maximum RAM supported	32 GB	Depth *	279.6 mm
Memory slots	2	Height *	188.2 mm
Internal memory *	16 GB	Weight	7.06 kg
Flash memory	4000 MB	Packaging content	
Network		Cables included	AC, LAN (RJ-45)
Ethernet LAN *	✓	Quick installation guide	✓
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Processor special features	
Ethernet LAN data rate supported (max)	10000 Mbit/s	Embedded options available	✗
Wi-Fi	✗	Enhanced Intel SpeedStep Technology	✓
DHCP client	✓	Execute Disable Bit	✓
DHCP server	✓	Idle States	✓
Jumbo frames support	✓	Intel 64	✓
iSCSI support	✓	Intel Clear Video Technology	✓
Wake-on-LAN ready	✓	Intel Enhanced Halt State	✓
Supported network protocols	TCP/IP, IPv4, IPv6	Intel Identity Protection Technology version	1.00
Dynamic DNS (DDNS)	✓	Intel Secure Key Technology version	1.00
WLAN adapter supported	✓	Intel Stable Image Platform Program (SIPP)	✗
Ports & interfaces		Intel Trusted Execution Technology	✗
USB port *	✓	Intel TSX-NI	✗
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Intel TSX-NI version	0.00
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Intel Virtualization Technology (VT-x)	✓
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Intel Virtualization Technology for Directed I/O (VT-d)	✓
HDMI ports quantity	1	Intel VT-x with Extended Page Tables (EPT)	✓
Ethernet LAN (RJ-45) ports *	3	Intel® AES New Instructions (Intel® AES-NI)	✓
Thunderbolt 3 ports quantity	2	Intel® Clear Video HD Technology (Intel® CVT HD)	✓
3.5 mm (1/8-inch) out	✓	Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID)	✓
PCI Express x4 (Gen 3.x) slots	1	Intel® Hyper Threading Technology (Intel® HT Technology)	✗
Microphone in	✓	Intel® Identity Protection Technology (Intel® IPT)	✓
Graphics		Intel® InTru™ 3D Technology	✓
On-board graphics card base frequency	350 MHz	Intel® OS Guard	✓
On-board graphics card dynamic frequency (max)	1050 MHz	Intel® Quick Sync Video Technology	✓
On-board graphics card ID	0x3E92	Intel® Secure Key	✓
Maximum on-board graphics card memory	64 GB	Intel® Turbo Boost Technology	2.0
Number of displays supported (on-board graphics)	3	Maximum number of PCI Express lanes	16
Design		Thermal Monitoring Technologies	✓
Chassis type *	Tower	Thermal solution specification	PCG 2015A
Cooling type *	Active	Memory channels supported by processor	Dual
Product colour	Black	Memory types supported by processor	DDR4-SDRAM
Number of fans	4 fan(s)	Operational conditions	
Fan diameter	12 cm	Operating temperature (T-T)	0 - 40 °C
Fan diameter 2	6 cm		
LED indicators	HDD, LAN, USB		
Built-in display	✓		
Cable lock slot	✓		
Cable lock slot type	Kensington		

Design		Operational conditions	
Built-in speaker(s)	✓	Operating relative humidity (H-H)	5 - 95%
Number of built-in speakers	1	Other features	
		Digital Living Network Alliance (DLNA) certified	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date