

FCS-5202, GEMINI Fixed IP Camera, 4-MP, 802.3af PoE, Indoor/Outdoor, IR LED

Product Images



Short Description

- 4-Megapixel high-definition resolution

- Video compression: H.264, H.265, MJPEG
- Weatherproof IP67-rated housing
- Supports motion detection (Intrusion/camera tampering/line crossing) and event notification

Description

The LevelOne FCS-5202 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 4-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5202 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Color	White
EAN	4015867207758
Model Number	FCS-5202
Features	Security: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface Network Storage: NAS (NFS, SMB/CIFS), auto network replenishment (ANR) Image Enhancement : BLC, HLC, 3D DNR Image Settings: Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser. Basic Event: Motion detection (human and vehicle targets classification), video tampering alarm, exception. Face Detection: Yes Perimeter Protection: Line crossing detection, intrusion detection Supports human and vehicle targets classification
Zoom type	Fixed
Camera Type	Bullet
PoE Supported	Yes
IR LED for night vision	Yes
Max. Resolution	4 Megapixels
Resistance	Weatherproof, Vandalproof
IP Camera series	GEMINI
Compatibility	Optional Accessory : CAS-7311 Junction box Plug-in required live view: IE 10, IE 11 Plug-in free live view : Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+ Web page support 33 languages English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian
Supported browsers	

Storage temperature	-40°C ~ 75°C
Storage humidity	0% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Approval and Compliance	CE/FCC FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015) UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950- 1:2005 + Am 1:2009 + Am 2:2013); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015) CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
Operating humidity	0% RH ~ 95% RH
Package Contents	serew Kit
Product weight (kg)	0.49
Dimensions (W x D x H)	Ø70 × 161.7 mm (Ø2.76" × 6.37")
Power consumption	12 VDC, 0.5 A, max. 6 W PoE (802.3af, 36 V to 57 V), 0.2 A to 0.13 A, max. 7 W
Resolution	Main Stream: 50Hz: 25fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60Hz: 30fps (2688 × 1520, 1920 × 1080, 1280 × 720) Sub Stream: 50Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360) Third Stream: 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360) 60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)
Port Configuration	RJ-45/Power jack
Shutter time	1/3 s to 1/100,000 s
Angle of view (°)	horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100°
IR cut filter	Yes
Standards	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, WebSocket, WebSockets
Lens	M12 /F1.6, 4mm
Indicators	Link/Power
Image sensor	1/3" Progressive Scan CMOS
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Mount	Wall mount
Storage capacity	Built-in microSD solt , up to 512 G
Digital zoom	8X
IR range	30 Meter
Weatherproof rating	IP67
Video format	MPEG4

