

ProDockExtreme® Gen 2

Universal USB-C to 4K HDMI, 4K DisplayPort® Dual Screen



Display Video, Charge Devices and Transfer Data effortlessly from USB-C Devices!

Features:

- ✓ 4K Enabled for HDMI® & DisplayPort™
- ✓ Dual Screen, Mirror and Extend (Windows compatible only)
- ✓ Dual Screen and Mirror (Mac compatible)
- ✓ 2 x USB 3.0
- ✓ SD Reader
- ✓ USB-C
- ✓ 3.5mm Audio
- ✓ Gigabit Ethernet
- ✓ 100W Power Delivery
- ✓ Integrated USB 3.1 Type-C Gen 2 cable
- ✓ Light-weight, portable design
- ✓ Windows, MAC & Android compatible

Simple, Effective USB-C Connectivity

The ProDockExtreme® Universal USB-C to HDMI & DisplayPort® Docking Station provides a simple and effective connectivity solution for charging, data transfer and video display from USB-C devices. Users can choose between single 4K HDMI®, single 4K DisplayPort® or dual screen, mirror and extend for video output, with 100W power delivery from USB-C port.

Display, Charge, and Transfer with Ease

HDMI port supports video resolution up to 4K/2K@30z, both video and audio support HDCP1.4 and 3D video format at 1920/1080p@60Hz. DisplayPort® support video up to 4K/2K@30Hz, supporting both displays simultaneously.

Transfer data with ease and speed, with a 10Gbs USB-C data port and 5Gbs USB 3.0, both USB 3.0 ports can be used at the same time, both ports also support 5V 1.5A fast charge for external devices.

Portable and lightweight, the ProDockExtreme® is ideal for charging, data transfer, and video displays in virtually any working environment.

Part Code: HYP-USBCPD-X2





- 1** USB-C M/M Cable (10cm)
- 2** HDMI® 4K (Single Screen)
- 3** Gigabit Ethernet
- 4** USB-C Power Delivery & Data

- 5** SD Reader SD 2.0 480Mbps(60MB/s)
- 6** 2 x USB 3.0 (Supports USB 2.0)
- 7** DisplayPort™ 4K (Single Screen MST)
- 8** 3.5mm Audio

| Port Type | Function | Details |
|-------------------------|-------------------|--|
| HDMI | Video Output | Up to 3840x2160@30Hz (single), 1920x1080@60Hz (dual) HDCP 1.4, 3D support |
| DisplayPort | Video Output | Up to 3840x2160@30Hz (single), 1920x1080@60Hz (dual) |
| USB-A 3.0 (x2) | Data & Charging | 5Gbps data speed 5V/0.9A charging up to 1.9A with PD backward compatible |
| USB-C Female | Power & Data | PD 3.0 charging (up to 85W) 5Gbps data speed when not charging |
| USB-C Male | Device Connection | Connects to USB-C PCs/phones no data or power transmission |
| RJ45 Ethernet | Network | 10/100/1000Mbps supports PXE boot and Wake-on-LAN |
| SD Card Slot | Storage | SD 2.0 up to 480Mbps (60MB/s) data speed |
| 3.5mm Audio Jack | Audio In/Out | Stereo output and MIC input supports 48KHz / 44.1KHz sampling |

Visit our website for or more information about the ProDockExtreme Gen 2.