


PIN OUT



Model No.	Length
118972	1.8M
118973	3M

Notes:

- Electronic Tests:
  - 100% OPEN/SHORT/INTERMITTENCE
  - Insulation Resistance: DC 300V 10M OHM
  - Conductitive Resistance: 3 OHM
- RoHS Compliant
- Marking: DVI DIGITAL DUAL LINK

⑦	FERRITE	14.2*28.5*8.0mm	2	PCS	
⑥	OUTER MOULD	45P, PVC, Black	47	G	
⑤	INNER MOULD	LDPE	8.2	G	
④	SCREW	Nickel Plated, Ø4.0mm*L:42mm, Black PVC	2	PCS	
③	CONNECTOR	DVI 24+1 Female, Pin Gold, Shell Nickel Plated, with Nuts	1	PC	
②	CONNECTOR	DVI 24+1 Male, Pin Gold, Shell Nickel Plated	1	PC	
①	CABLE	30AWG(7/0.10BC*1P+1/0.254CCS+HDPE+AL)*7+1/0.254CCS*5C+AL+1/0.254CCS+112/0.12AL-MG, BLACK JACKET, OD:7.3±0.2MM	1800	MM	
S/N.	P/N.	SPECIFICATIONS	QTY	UNIT	REMARKS

DVI-D Dual Link Male to Female Cable

