



# **HSM SECURIO B22 - 1.9 x 15 mm**


## **HSM SECURIO B22 document shredder**

Data security made easy! The powerful entry level model of the B-series for the workplace. With automatic start/stop and overload protection. The waste container with 33 litres of capacity can be easily removed and emptied.

# **Technical data**

Order number:	1832821	Intake width:	240 mm
EAN	4026631049290	Container volume /	33
Cutting type:	particle cut	collecting:	
Cutting size:	1,9 x 15 mm	Collection volume in sheets (80 g):	420
Security level (DIN 66399):	E-4 F-2 P-5 T-5	Noise level (idle operation):	ca. 57 dB(A)
Cutting capacity in sheets 80g/m <sup>2</sup> :	7 - 9	Width x Depth x Height:	375 x 310 x 600 mm
•		Weight:	12,477 kg
Power consumption:	440 W	Shredder material:	Danes Charles and sames
Voltage / Frequency:	230 V / 50 Hz	Sifreduer material:	Paper, Staples and paper clips, Credit card

## **Product information**



The induction-hardened, solid steel cutting rollers guarantee durability.




The full bin is indicated via the display and the machine switches off automatically.



The waste container can be easily removed and emptied.





#### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



#### **Energy-saving**

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



# High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



## **Automatic start/stop**

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



## Display bin full

The full bin is indicated via the display and the machine switches off automatically.



## Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).







