



# HSM SECURIO B34 - 5.8 mm


## **HSM SECURIO B34 document shredder**

This premium document shredder in an elegant design provides for data security in an open-plan office. Thanks to the powerful drive, it reliably and quietly shreds the incoming amounts of data of up to eight people.

# **Technical data**

Order number:	1841811	Intake width:	310 mm
EAN	4026631028042	Container volume /	100
Cutting type:	strip cut	collecting:	
Cutting size:	5,8 mm	Collection volume in sheets (80 g):	658
Security level (DIN 66399):	E-2 O-2 P-2 T-2	Noise level (idle operation):	ca. 56 dB(A)
Cutting capacity in sheets 80g/m²:	30 - 32	Width x Depth x Height:	541 x 439 x 845 mm
		Weight:	34,5 kg
Power consumption:	700 W	Show data was a tradely	
Voltage / Frequency:	220-240 V / 50 Hz	Shredder material:	Paper, Staples and paper clips, Credit card, CD/DVD

## **Product information**



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



The full bin is indicated via the display and the machine switches off automatically.





#### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



#### **Energy-saving**

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



#### High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



### **Automatic start/stop**

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



# Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



# **Convenient emptying**

Robust wooden cabinet with castors. After opening the door, the reusable collecting bag can be easily removed and emptied.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).









