



## 24-Port Gigabit PoE Switch, 802.3at/af PoE

The LevelOne GEP-2421 series are unmanaged Gigabit PoE switches with 24 RJ45 PoE ports. The switches are IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with a total power budget of 150/250/380/500/630W, or up to 30W per port. Ideal for desktops, they are also 19-inch rack-mountable, which provides convenient and flexible installation. The GEP-2421 switches are designed for small-to-medium businesses that require an affordable solution for deploying PoE infrastructure.

### Key Features

- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 10K jumbo frames to increase data transfer rates
- Supports 8K MAC address auto-learning and auto-aging
- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- 19-inch rackmount kit included

### Specifications

#### System Specifications

##### Standards & Protocols:

IEEE 802.3 10-BASE-T (Ethernet)  
IEEE 802.3u 100-BASE-TX (Fast Ethernet)  
IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)  
IEEE 802.3x Flow Control (full-duplex flow control)  
IEEE 802.3az (Energy Efficient Ethernet)  
IEEE 802.3af Power over Ethernet  
IEEE 802.3at Power over Ethernet Plus

##### Memory:

MX25L4005AMC-12G

##### Buffer Memory:

4.1Mbit

##### Connectors and Cabling:

24\*RJ45

##### Button/Knob:

POWER Button

**Indicator:**

Power,LAN 1~24 port, PoE 1~24 port

**Transmission Method:**

10Base T Cat. 3, 4, 5 UTP/STP

100Base TX Cat. 5 UTP/STP

1000Base TX Cat. 5e/6/7 UTP/STP

**Power Input:**

AC Power input(100V~240V), 50-60 Hz

**Power Output:**

Per Port 56VDC, Max. 30 watts (802.3at)

**Power Consumption:**

150W/250W/380W/500W/630W

**Backplane (Gbps):**

48Gbps

**MAC Address Table:**

8K

**Data Transfer Rate:**

10/100/1000Mbps

## Features

**General:**

24-port Gigabit Ethernet with

24-port 802.3at/af PoE Switch

**PoE:**

IEEE 802.3at/af Power over Ethernet/PSE Mode A

## Performance

**Packet Forwarding Rate:**

10Mbps 14880pps,

100Mbps 148800pps,

1000Mbps 1488000pps

**Jumbo Frame (K):**

10K

**Switching Capacity:**

48Gbps

## Environment

**Power Saving:**

IEEE 802.3az (Energy Efficient Ethernet)

**Heat Dissipation:**

FAN

**Temperature (°C):**

0° ~ 50°C

**Humidity (Non-condensing):**

10 ~ 90%

**Installation:**

Rackmount

## Physical Specifications

### Dimensions (W x D x H mm):

440x220x44

### Weight (g):

3.8kg

## Reliability

### MTBF:

55.5khours (6 years)

## Approval and Compliance

### EMI/EMS:

#### EMI:

EN55032:2012+AC:2013

EN55022:2010+AC:2011

AS/NZS CISPR 22 Amdt. (2010)

EN61000-3-2:2014

EN61000-3-3:2013

#### EMS:

EN55024:2010

IEC61000-4-2:2008

IEC61000-4-3:2006+A1:2007+A2:2010

IEC61000-4-4:2012

IEC61000-4-5:2005

IEC61000-4-6:2013

IEC61000-4-8:2009

IEC61000-4-11:2004

### Safety:

FCC Class A, CE

### Environmental Test:

Operating Temperature 0° ~ 50°C

Storage Temperature -20 to 70 °C

---

## Order Information

GEP-2421W150: 150W

GEP-2421W250: 250W

GEP-2421W380: 380W

GEP-2421W500: 500W

GEP-2421W630: 630W

---

## Package Contents

GEP-2421W150

User Manual

Rubber Feet

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.