



34-Port Fast Ethernet PoE Switch, 32 PoE Outputs, 2 x Gigabit RJ45

The LevelOne FGP-3400 series are unmanaged PoE switches with 32 RJ45 PoE ports. The switches are IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with a total power budget of 250/380/500/630/760W, or up to 30W per port. Ideal for desktops, they are also 19-inch rack-mountable, which provides convenient and flexible installation. The FGP-3400 switches are designed for small-to-medium businesses that require an affordable solution for deploying PoE infrastructure.

Key Features

- PoE on/off control per port by dip switches
- IEEE 802.3af/at PoE PSE with 30W power budget
- IEEE 802.3af PoE compliant to simplify deployment and installation
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 19-inch rackmount kit included

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T (Ethernet)
IEEE 802.3u 100-BASE-TX (Fast Ethernet)
IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)
IEEE 802.3x Flow Control (full-duplex flow control)
IEEE 802.3af Power over Ethernet
IEEE 802.3at Power over Ethernet Plus

Buffer Memory:

8Mbit

Connectors and Cabling:

32 x 10/100Base-TX RJ-45 PoE Ports
2 x 10/100/1000Base-T RJ-45 Ports

Button/Knob:

POWER Button

Indicator:

Power, Uplink, LAN 1~32 port, PoE 1~32 port

**Transmission Method:**

10Base T Cat. 3, 4, 5 UTP/STP
100Base TX Cat. 5 UTP/STP
1000Base TX Cat. 5e/6/7 UTP/STP

Power Input:

AC Power input(100V~240V), 50-60 Hz

Power Output:

Per Port 56VDC, Max. 30 watts

Power Consumption:

250W/380W/500W/630W/760W

Backplane (Gbps):

10.4Gbps

MAC Address Table:

32K

Data Transfer Rate:

10/100/1000Mbps

Features

PoE:

IEEE 802.3at/af Power over Ethernet/PSE Mode B

Performance

Packet Forwarding Rate:

10Mbps 14880pps,
100Mbps 148800pps,
1000Mbps 1488000pps

Jumbo Frame (K):

16K

Switching Capacity:

10.4Gbps

Environment

Heat Dissipation:

FAN

Temperature (°C):

Operating Temperature 0° ~ 40°C
Storage Temperature -20 to 70 °C

Humidity (Non-condensing):

Operating: 10 ~ 90%
Storage: 10 ~ 90%

Physical Specifications

Dimensions (W x D x H mm):

442 x 197 x 43

Weight (g):

2000

Reliability

MTBF:
74khours (8 years)

Approval and Compliance

EMI/EMS:

EMI:

EN55032:2012+AC:2013

EN55022:2010+AC:2011

AS/NZS CISPR 22 Amdt. (2010)

EN61000-3-2:2014

EN61000-3-3:2013

EMS:

EN55024:2010

IEC61000-4-2:2008

IEC61000-4-3:2006+A1:2007+A2:2010

IEC61000-4-4:2012

IEC61000-4-5:2005

IEC61000-4-6:2013

IEC61000-4-8:2009

IEC61000-4-11:2004

Safety:

FCC Class A, CE

Order Information

FGP-3400W250: 250W

FGP-3400W380: 380W

FGP-3400W500: 500W

FGP-3400W630: 630W

FGP-3400W760: 760W

Package Contents

FGP-3400W250

Power Cord

Rubber Feet

Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.