



WAP-8123 Version: 1

## AC1200 Dual Band PoE Wireless Access Point, Ceiling Mount, Controller Managed

LevelOne's WAP-8123 is a managed, dual-band wireless access point, Supply 802.11ac Wave 2 MU-MIMO (Multi-User Multiple-Input Multiple-Output), allows multiple devices to get high- bandwidth Wi-Fi signal at the same time, distributing data more efficiently. capable of a combined speed of up to 1200 Mbps. The device runs on 2.4 and 5 GHz frequencies, and can be used as part of a managed network when controlled by the LevelOne WAC-2000/WAC-2003 Wireless LAN Controller. LevelOne WAP-8123 also offers PoE, removing the need for an external power supply, which makes it easy to install. A fast, versatile and secure access point for a wide variety of network requirements.

### Key Features

- Share your wireless network up to 1200Mbps
- Compatible with IEEE 802.11a/b/g/n/ac Wave 2 wireless standards
- MU-MIMO technology greatly enhances WLAN performance for all clients
- Dual power support: 12V DC/PoE (IEEE 802.3at)
- Multi-operation modes to suit different wireless applications
- Auto Channel Selection for low interference band
- Provides up to 8 SSIDs to separate network traffic and enhance security
- High power and receiver sensitivity designed to boost your signal coverage and link speed

### Specifications

#### System Specifications

##### Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet  
IEEE 802.3u 100-BASE-TX, Fast Ethernet  
IEEE 802.11e Wi-Fi Multimedia (WMM)  
IEEE 802.3x Ethernet Flow Control  
IEEE 802.11i Wi-Fi Protected Access (WPA2)  
IEEE 802.11a/b/g/n/ac  
IEEE 802.11ac Wave 2 MU-MIMO  
IEEE 802.3at Power over Ethernet  
IEEE 802.3az

##### Port:

1x 10/100/1000Mbps WAN port  
1x 10/100/1000Mbps LAN port  
1x 12V DC Port



**Button/Knob:**  
1x Reset Button

**Indicator:**  
Power, System status

**Power Input:**  
Power over Ethernet (IEEE802.3at) 48VDC  
External power adapter: 12V/1.5 A (not included)

**Power Consumption:**  
< 30W

## Wireless

### Operating Mode:

Gateway Mode  
Repeater Mode  
AP Mode  
WISP Mode

### Encryption:

WEP 64/128-bit Web share key encryption  
WPA, WPA2 128-bit TKIP/AES encryption  
WPA, WPA2-PSK TKIP/AES encryption

### Receive Sensitivity(dBm):

#### 2.4 GHz Radio :

802.11b / 1Mbps / RX Sensitivity : -94 (dBm)  
802.11b / 11Mbps / RX Sensitivity : -85 (dBm)  
802.11g / 6Mbps / RX Sensitivity : -90 (dBm)  
802.11g / 54Mbps / RX Sensitivity : -72 (dBm)  
802.11n HT20 / MCS0 / RX Sensitivity : -88 (dBm)  
802.11n HT20 / MCS7 / RX Sensitivity : -70 (dBm)  
802.11n HT40 / MCS0 / RX Sensitivity : -86 (dBm)  
802.11n HT40 / MCS7 / RX Sensitivity : -68 (dBm)

#### 5.8 GHz Radio :

802.11a HT20 / 6Mbps/ RX Sensitivity : -90 (dBm)  
802.11a HT20 / 54Mbps/ RX Sensitivity : -72 (dBm)  
802.11n HT20 / MCS0 / RX Sensitivity : -88 (dBm)  
802.11n HT20 / MCS7 / RX Sensitivity : -70 (dBm)  
802.11n HT40 / MCS0 / RX Sensitivity : -86 (dBm)  
802.11n HT40 / MCS7 / RX Sensitivity : -68 (dBm)  
802.11ac VHT80 / MCS0 / RX Sensitivity : -85 (dBm)  
802.11ac VHT80 / MCS9 / RX Sensitivity : -58 (dBm)

### Wireless Channels:

#### 2.4 GHz :

Ch.1 ~ 11 USA  
Ch.1 ~ 13 EU

#### 5.8 GHz :

Ch.36~64 , 100~128 , 132~140 , 149~165 USA  
Ch.36~64 , 100~128 , 132~140 EU

### EIRP(dBm):

2.4 GHz Radio: EIRP < 20dBm  
5.8 GHz Radio: EIRP < 20dBm

### Antenna:

2x 2.4 GHz Build in 5dBi MIMO Antenna  
2x 5.8 GHz Build in 5dBi MIMO Antenna

**Frequency Band:**

2.4 ~ 2.4835 GHz

5.15 ~ 5.35 GHz

5.46 ~ 5.72 GHz

5.725~ 5.825 GHz

**Modulation:**

OFDM = BPSK,QPSK, 16-QAM, 64-QAM, 128-QAM, 256-QAM

DSSS = DBPSK, DQPSK, CCK

**Data Transfer Rate:**

802.11ac : 866.7Mbps

802.11n: 300 Mbps

802.11g: 54 Mbps

802.11b: 11 Mbps

## Features

**General:**

Multi-SSID: 8 SSIDs (2.4GHz x 4 SSIDs + 5.8GHz x 4 SSIDs)

**PoE:**

IEEE 802.3at

**Security:**

SSID Broadcast On/Off

Tag VLAN

**Management:**

WEB interface

**QoS:**

802.11e WMM Supported

**Ease of Use:**

Web-based GUI with Quick Installation Wizard

Web-based (HTTP) firmware upgrade

## Performance

**Number of Clients:**

Maximum: 128

Recommend: 100

## Environment

**Operating Temperature (°C):**

-30°C~55°C

**Operating Humidity (Non-condensing):**

10 ~ 90%

**Storage Temperature (°C):**

-40°C~70°C

**Storage Humidity (Non-condensing):**

5%~95%

**Installation:**

Ceiling Mount

## Physical Specifications



**Dimensions (W x D x H mm):**

198 x 198 x 28 mm

**Weight (g):**

521 g

## Approval and Compliance

**EMI/EMS:**

CE,FCC

---

## Order Information

WAP-8123

---

## Package Contents

WAP-8123

Screw Kit

RJ45 Network Cable

Quick Installation Guide

Resource CD (User Manual, QIG)

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.