



FVT-1104 Version: 1

RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 1310nm, 60km

The LevelOne FVT-1104 single-mode fiber optic media converter with SC connection is ideally suited to convert network signals between copper and fiber optic based networks. The converter has a 10/100Base-TX RJ-45 port, supports full-duplex and half-duplex switch connectivity as well as 10Base-T and 100Base-TX auto-sensing. Single-mode fiber optic cables bridge distances of up to 60 km. The converter can be used either stand-alone or as a plug-in module for the CHV-2000 19" chassis, which can accommodate up to 14 converters for use in a central data distributor.

Key Features

- Supports the transmission of extra-long packets up to 1.6KB
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Single-mode fiber with SC connector for transmission of up to 60km
- Supports low-time lag transmission

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3x Flow Control (full-duplex flow control)

Port:

1 x 100Base-FX Single-mode duplex SC
 Fiber cable: 50/125um, 62.5/125um
 1 x 10/100Base-TX RJ-45 Port, auto MDI/MDI-X and Auto-Negotiation

Indicator:

PWR, TX (FDX, 100, Link/Act), FX (100, Link/Act)

Wavelength (nm):

1310nm

Transmission Method:

Store and forward (Default)

Power Input:

DC 5V/1A



Performance

Operating Distance:
60KM

Environment

Operating Temperature (°C):
0°C to 50°C

Operating Humidity (Non-condensing):
-20°C to 70°C

Storage Temperature (°C):
-20°C to 70°C

Installation:
Desk, chassis mounted

Physical Specifications

Dimensions (W x D x H mm):
71 x 94 x 26 mm

Weight (g):
420 g

Reliability

MTBF:
100,000 hours

Approval and Compliance

EMI/EMS:
CE, RoHS

Order Information

FVT-1104

Package Contents

FVT-1104
Power Adapter
Quick Installation Guide

Optional Accessory



CVH-2000
14-Slot Media Converter Chassis

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.