



KRONE 45°-110 DUAL IDC

RJ45 RIGHT ANGLE JACK

SCALE 1/4

Specification :

- Material :
1. Panel : SECC, 1.2 mm thickness with Light Grey (RAL-7035).
  2. RJ45 Jack :
    - 2-1. Housing : PBT+Glass Fiber, UL 94V-0.
    - 2-2. Contact Bracket : PBT+Glass Fiber, UL 94V-0.
  3. RJ45 Jack Contact :
    - 3-1. Material : Phosphor Bronze with Nickel plated.
    - 3-2. Finish : 50 micro-inch Gold plated on Plug contact area.
  4. RJ45 Jack Shield : Bronze With Nickel plated.
  5. IDC :
    - 5-1. Housing : PC+Glass Fiber, UL 94V-2.
    - 5-2. Terminal : Phosphor Bronze with Tin plated.
  6. PCB : FR4, UL 94V-0.

- Performance :
- a. T568A & T568B wiring printing on IDC.
  - b. Insertion force : 30N max. (IEC 60603-7-5)
  - c. Retention strength : 7.7 kg between Jack and Plug.
  - d. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA568 B.2)
  - e. Life(mating cycles) :
    - \*Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5)
    - \*IDC : Suitable for 22-26 AWG stranded and solid wire, Compatible with both 110 & Krone punch down tools.
  - f. The Cat.6 transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2-1 standard.

326316

16 Ports CAT.6 Shielded Patch Panel