# TRENDnet®

4-Port Dual Monitor DisplayPort KVM Switch

TK-440DP (v1.0R)

- Dual Monitor DisplayPort™ 1.2 KVM
- 3.5mm speaker and microphone connections
- Designed for use with Dual DisplayPort systems
- Supports 4K UHD resolutions up to 3840 x 2160 @ 60Hz
- 2-Port USB 2.0 hub for storage devices and printers
- Required cabling sold separately (TK-CP06)
- No CD installation required

TRENDnet's 4-Port Dual Monitor DisplayPort KVM Switch, model TK-440DP, allows you to control four computers with one set of console controls. Experience up to 4K UHD resolutions, no driver installation required. The TK-440DP is designed for dual monitor systems with USB mouse and keyboard connections, and features a two-port USB hub to share storage devices or printers between computers.

TRENDnet®

Dual Monitor
Designed to connect to two DisplayPort monitors.

4K UHD Resolution
Supports resolutions up to 4K UHD (3840 x 2160 @ 60Hz).

USB 2.0 Hub
Two additional USB ports to connect storage drives and printers.

NETWORKING SOLUTION

PC 4
PC 3
PC 2
PC 1
Monitor 1
Monitor 2
Keyboard
Mouse

Console Port Connectors

KVM Port Interface

DisplayPort 1.2

4 x Computers

USB 2.0 Hub

Power port

Dual DisplayPort USB KVM Switch
TK-440DP

PC select buttons

Keyboard

Mouse

Microphone / speaker jacks

USB Type B to PC

Microphone / speaker jacks

DisplayPort 1.2

FEATURES

4-Port Dual Monitor KVM
Control up to four computers with dual monitor support

DisplayPort Monitor
Designed to connect to two DisplayPort monitors

4K UHD
Supports resolutions up to 4K UHD (3840 x 2160 @ 60Hz)

Audio Support
Full audio support maximizes work station productivity

USB Mouse & Keyboard
True Transparent USB (TTU) emulation technology supports most keyboard and mouse designs

Housing
Rugged metal enclosure

USB 2.0 Hub
Two additional USB ports to connect storage drives and printers

Hot Keys
Hot Key command shortcuts

Easy Installation
Simple setup with driverless installation

SPECIFICATIONS

Console Port Connectors
- Keyboard: USB Type A
- Mouse: USB Type A
- Monitors: 2 x DisplayPort 1.2
- 2-port USB 2.0 Hub
- Speaker jack: 3.5mm
- Microphone jack: 3.5mm

KVM Port Interface
- Keyboard/Mouse: USB Type B
- Monitors: 2 x DisplayPort 1.2
- Speaker jack: 3.5mm
- Microphone jack: 3.5mm

Computer Interface (up to 4)
- Keyboard/Mouse: USB Type A
- Monitors: 2 x DisplayPort 1.2
- Speaker jack: 3.5mm
- Microphone jack: 3.5mm

Monitor Resolution
- Up to 3840 x 2160 @ 60Hz

Switching Control
- Front panel push buttons
- Keyboard hot key commands

Operating Temperature
- 0° – 40° C (32° – 104° F)

Operating Humidity
- Max. 90% non-condensing

Power
- Input: 100 – 240V AC, 50/60Hz, 0.8A
- Output: 9V DC, 2A external power adapter
- Max. consumption: 0.7W

Dimensions (L x W x H)
- 254 x 100 x 66mm (10 x 3.9 x 2.6 in.)

Weight
- 1.2kg (2.7 lbs.)

Warranty
- 2 year

Certifications
- CE
- FCC

Package Contents
- TK-440DP
- Quick Installation Guide
- Power adapter (9V DC, 2A)

Updated: 9/18/2019