



TS-431XeU-8G CPU AnnapurnaLabs Alpine AL314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor **CPU** Architecture 32-bit ARM **Floating Point Unit** Yes **Encryption Engine** Yes 8 GB SODIMM DDR3 (1 x 8 GB) System Memory Maximum Memory 8 GB (1 x 8 GB) **Memory Slot** 1 x SO-DIMM DDR3 **Flash Memory** 512MB (Dual boot OS protection) **Drive Bay** 4 x 3.5-inch SATA 6Gb/s, 3Gb/s **Drive Compatibility** 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes SSD Cache Acceleration Yes Support **Gigabit Ethernet Port** 2 (RJ45) 1 x 10GbE SFP+ 10 Gigabit Ethernet Port Wake on LAN (WOL) Yes Jumbo Frame Yes 4 USB 3.2 Gen 1 port **Form Factor 1U Rackmount LED** Indicators HDD 1-4, Status, USB, LAN1-3 **Buttons** Power, Reset

Dimensions (HxWxD)	44 × 439 × 291 mm
Weight (Net)	4.15 kg
Weight (Gross)	5.78 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	Open-frame 100W, Input: 100V-240V ~ / 3.5A, 50Hz-60Hz
Power Consumption: HDD Sleep Mode	12.42 W
Power Consumption: Operating Mode, Typical	30.99 W
Fan	3 x 40mm, 12VDC
Sound Level	20.3 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. * Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.