

OZUL01B 4-Port 65W Desktop USB PD Charger with AC power cable, USB-C x 1, USB-A x 3, QC 3.0, PD 3.0

Product Images





Short Description

- **Versatile Port Selection:** Equipped with 4 ports including 1 USB-C ports (with PD 3.0) and 3 USB-A ports (with QC 3.0), providing up to 65W and allowing simultaneous charging for multiple devices with varying power requirements.
- **Wide Compatibility:** Supports a range of output options from 3.6V to 20.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- **Efficiency and Fast Charging Technology:** Incorporates USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies, ensuring broad compatibility and rapid charging for many devices.

Description

This charger is equipped with a versatile port selection, including 1 USB-C port with Power Delivery (PD) 3.0 and 3 USB-A ports with Quick Charge (QC) 3.0, providing up to 65W and allowing simultaneous charging for multiple devices with varying power requirements. It supports a range of output options from 3.6V to 20.0V across its ports, ensuring compatibility with devices from smartphones to laptops. Enhanced safety features include built-in protections against overload, short-circuiting, and overheating, ensuring the safety of both the charger and the connected devices. Incorporating both USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies, this charger ensures broad compatibility and rapid charging for many devices.

Additional Information

Port Configuration	USB-C PD x 1, USB-A QC 3.0 x 1, USB-A x 2
Number of outputs	4
USB Type-A ports quantity	3
Fast charging technology	Quick Charge 3.0, Power Delivery 3.0
USB Type-C ports quantity	1
Programmable power supply (PPS) (YES/NO)	No
Housing Material	Polycarbonate (PC)
Number of simultaneously connected devices (max)	4
Port 1 Power Output	USB-C output: DC 5.0V/3.0A, 9.0V/3.0A, 12.0V/3.0A, 15.0V/3.0A, 20.0V/3.25A
Port 2 Power Output	USB-A1 output: DC 3.6-6.0V/3.0A, 6.0-9.0V/2.0A, 9.0-12.0V/1.5A(QC 3.0)
Port 3 Power Output	USB-A2 output: DC 5.0V/2.4A
Port 4 Power Output	USB-A3 output: DC 5.0V/2.4A
Power Plug Type	EU
Number of cartons per pallet	16 piece
Package volume	1254 cubic_centimeter
Pallet net length	800 millimeter
Pallet net width	1200 millimeter
Pallet net height	1440 millimeter
Quantity per pack	1 piece
Package Depth	190 millimeter
Package Height	55 millimeter
Package Width	120 millimeter
Package Weight	33 gram
Harmonized System (HS) code	850440

Customs product code (TARIC)	8504408390
Quantity per pallet	800 piece
Sustainability compliance	No
Approval and Compliance	CE, RoHS
Operating humidity	10% RH ~ 80% RH
Operating temperature	0°C ~ 40°C
Package Content	Quick installation guide, Foot Stand
Storage humidity	5% RH ~ 95% RH
Storage temperature	-20°C ~ 80°C
Package Contents	OZUL01B AC power cable Foot stand Multilingual quick installation guide
USB Power Delivery revision	3.0
Operating temperature (T-T) Max	40 celsius
Operating temperature (T-T) Min	0 celsius
Storage relative humidity (H-H) Max	95%
Storage relative humidity (H-H) Min	5%
Operating relative humidity (H-H) Max	80%
Operating relative humidity (H-H) Min	10%
Storage temperature (T-T) Max	80 celsius
Storage temperature (T-T) Min	-20 celsius
Color	Black
EAN	4015867226377
Model Number	OZUL01B
Maximum AC Input	240 volt
Minimum AC Input	100 volt
Input current	1.6 ampere
Maximum power	65 watt
Icecat_Power protection features	Over current, Over power, Short circuit

Product Height	103 millimeter
Product Width	69 millimeter
Product Depth	27 millimeter
Product Weight	255 gram
Indicators	yes
Power input	AC 100-240V 50/60HZ, 1.6A Max
Dimensions (W x D x H)	69 x 27 x 103 mm
Product weight (kg)	0.255

