

605602 Cat.6A Platinum S/FTP Patch Cable, 3.0m , Grey

Product Images







Compliance Statement

Screened Category 6A ISO/IEC, EN & ANSI/TIA Communication Cable

Short Description

- 1. 4 x 2 AWG 26/7
- 2. 500MHz performance Bandwidth
- 3. Transmission: 10Gbit
- 4. Suitable for PoE, PoE+, PoE++
- 5. Stranded bare copper conductor
- 6. Foil and braid shield Reduces EMI/RFI interference
- 7. PIMF (Pairs in metal Foil)
- 8. Molded boot with Strain relief
- 9. RoHS compliant
- 10. Low Smoke Zero Halogen (LSZH/LSOH)
- 11. with 3P certificate and UL listed
- 12. Compliant with ISO/IEC 11801 and EN 50173

Description

Cat.6A Pro S/FTP Patch Cord is composed of preeminent materials and fully-examined to Cat.6A Platinum S/FTP Patch Cord is composed of preeminent materials and fully-examined to conform with industrial

2 1/27/23 standards. Offering higher bandwidth and better signal-to-noise margin, the Cat.6A cable is able to deliver ultrahigh and error-free performance in the most demanding network environments, specially for 10G application.

Additional Information

| Approval and compliance | RoHS, 3P |
|-------------------------|------------------------|
| Conductor material | Copper |
| Conductor size (AWG) | 26AWG |
| Jacket material | LSZH |
| Category | Cat.6A |
| Flat cable | No |
| Shielded | Yes |
| Product weight (kg) | 0,128 |
| Cable length | 3m |
| Color | Grey |
| EAN | 4015867163474 |
| Model number | 605602 |
| Package contents | 605602 |
| Cable Length | 3.0m |
| Shielding | S/FTP |
| Connector 1 | RJ45 male |
| Connector 2 | RJ45 male |
| Dimensions (W x D x H) | 8.34 x 11.68 x 3000 mm |

