

POI-5002W60 Gigabit PoE Injector, 802.3 af/at/bt, 60W

Product Images



Short Description

Auto-detection and protection of non-standard PoE devices

IEEE 802.3af/at/bt PoE compliant to simplify deployment and installation

Total PoE power budget: 60W,

Description

POI-5002W60 is a single port, high-power 60W PoE PSE solution for remote PoE PD devices. Generating up to 60W through 8 pins, POI-5002 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras, lighting, panel display for digital signage and video-phones. It complies to IEEE 802.3bt PoE standards to deliver 60W on both end-point and midspan pairs with a total power of 60W PoE output. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points.

Additional Information

Operating humidity

Operating temperature

Indicators Mount

Pin assignment and polarity

Power Output

Standards

Features

Product weight (kg)

Color EAN

Model Number Package Contents

Grade Data rate

Injector Port Type

Data rate

Dimensions (W x D x H)

0% RH ~ 95% RH

0°C ~ 40°C

Power, Mode A, Mode B

Wall mount

1/2 (+), 3/6 (-) & 4/5 (+), 7/8 (-)

60W

IEEE 802.3at/af/bt IEEE 802.3 10-BASE-T IEEE 802.3u 100-

BASETX IEEE 802.3ab 1000BASE-T

1-port GigE Ultra PoE Injector

0,53 Black

4015867223253 POI-5002W60

POI-5002W60 Power Cord

Commercial
Gigabit Ethernet
Single Port

10/100/1000Mbps

180 x 71 x 37 mm

